

DOUBLE PITCH WITH PLUMB CURB (SHORT SPAN)

1/2 FULL SCALE

- o GLASS, INSULATED GLAZED
- o I-BEAM RAFTER (HL-27)
- o MIN. 4 IN 12 PITCH RECOMMENDED

1/8" X 3/8"
BUTYL OR FOAM
GLAZING TAPE

HL-22 ALUM. CAP
MITERED & WELDED
AT CORNERS

#8 X 3/4" LONG HEX
HEAD TEK SCREW AT
24" O.C.

1/8" X 3/8" BUTYL
OR FOAM GLAZING
TAPE

MASTIC BEDDING
TAPE (BY OTHERS)

FASTENER
(BY OTHERS)

HL-34
ALUMINUM SILL

STRUCTURAL CURB
(BY OTHERS)

O.D. CURB

3
2

1/8" X 3/8" BUTYL OR
FOAM GLAZING TAPE

INSULATED
GLASS

#10 S.S. P.H.S.M.S.
WITH NEOPRENE
WASHER AT 12" O.C.

C-13 CAP

HL-27 ALUM.
RAFTER BAR

4
2

FINISH :	PROJECT :
GLAZING :	CUSTOMER :
<input type="checkbox"/> FIELD GLAZED FIELD MEASUREMENTS <input type="checkbox"/> SHOP GLAZED AND INSTALLATION BY _____	ARCHITECT :

FILE : HL34DIG2
REVISIONS

O'KEEFFE'S, INC.

75 WILLIAMS AVENUE
SAN FRANCISCO, CA 94124
TEL.: (415) 822-4222
FAX: (415) 822-5222

DRAWN :
DATE :

JOB NO.
SHEET : <u>2</u> OF <u>2</u>