

# DOUBLE PITCH WITH PERPENDICULAR CURB (SHORT SPAN)

1/2 FULL SCALE

- o GLASS, INSULATED GLAZED
- o I-BEAM RAFTER (HL-27)
- o MIN. 4 IN 12 PITCH RECOMMENDED

1/8" X 3/8"  
BUTYL OR FOAM  
GLAZING TAPE

HL-22 ALUM. CAP  
(ALLOY 6063-T5)  
MITERED & WELDED  
AT CORNERS

#8 X 3/4" LONG  
HEX HEAD TEK  
SCREW AT 24"  
ON CENTER

1/8" X 3/8"  
BUTYL OR FOAM  
GLAZING TAPE

MASTIC BEDDING  
TAPE (BY OTHERS)

FASTENER  
(BY OTHERS)

HL-34 ALUM. SILL  
(ALLOY 6063-T5)

MATERIAL AND  
CONSTRUCTION  
BY OTHERS

3  
2

O.D. CURB

1/8" X 3/8" BUTYL OR  
FOAM GLAZING TAPE


INSULATED  
GLASS

#10 S.S. P.H.S.M.S.  
WITH NEOPRENE  
WASHER AT 12" O.C.

C-13 CAP

HL-27 ALUMINUM  
(ALLOY 6063-T5)  
RAFTER BAR

4  
2

FINISH :		PROJECT :	FILE : HL34DIG4
GLAZING :		CUSTOMER :	REVISIONS
<input type="checkbox"/> FIELD GLAZED      FIELD MEASUREMENTS <input type="checkbox"/> SHOP GLAZED      AND INSTALLATION BY _____		ARCHITECT :	
 O'KEEFFE'S, INC.		75 WILLIAMS AVENUE SAN FRANCISCO, CA 94124 TEL.: (415) 822-4222 FAX: (415) 822-5222	JOB NO.
		DRAWN :	SHEET : 2 OF 2
		DATE :	