

1/8" x 3/8"
BUTYL OR FOAM
GLAZING TAPE

HL-22 ALUM.
CAP MITERED
AND WELDED
AT CORNERS

#8 X 3/4" LONG
HEX HEAD TEK
SCREW AT 24"
ON CENTER

MASTIC
BEDDING TAPE
(BY OTHERS)

FASTENER
(BY OTHERS)

HL-35 ALUM. SILL
(ALLOY 6063-T5)

MATERIAL AND
CONSTRUCTION
BY OTHERS

3
2

O.D. CURB

1/8" x 3/8" BUTYL OR
FOAM GLAZING TAPE

INSULATED
GLASS

WG-5 GASKET
OR GLAZING TAPE

#10 S.S. P.H.S.M.S.
WITH NEOPRENE
WASHER AT 12" O.C.

C-13 CAP


TB-300 OR TB-3
(ALLOY 6063-T5)
ALUM. RAFTER BAR

4
2

DOUBLE PITCH WITH PERPENDICULAR CURB (LONG SPAN)

- o GLASS, INSULATED
- o TUBULAR RAFTER (TB-300) OR (TB-3)
- o MIN. 4 IN 12 PITCH RECOMMENDED

1/2 FULL SCALE

FINISH :		PROJECT :	FILE : HL350IG6
GLAZING :		CUSTOMER :	REVISIONS
<input type="checkbox"/> FIELD GLAZED	FIELD MEASUREMENTS AND INSTALLATION BY _____	ARCHITECT :	
<input type="checkbox"/> SHOP GLAZED			
 O'KEEFFE'S, INC.		75 WILLIAMS AVENUE SAN FRANCISCO, CA 94124 TEL.: (415) 822-4222 FAX: (415) 822-5222	DRAWN :
			DATE :
			JOB NO.
			SHEET : <u>2</u> OF <u>2</u>